



▶ Non-Incendive Pointing Devices

HP-DT-NI

Technical Specifications

Features and Benefits:

- ▶ Desktop Model
- ▶ Meets NEMA 4, 4X Specifications
- ▶ Stainless Steel Case
- ▶ Industrial Silicone Rubber Overlay
- ▶ Right and Left Click, Plus Programmable Button
- ▶ Sensor Moves on 10 Degree Tilt for 360 degree movement
- ▶ Includes Bulkhead Connector

Also Available:

Panel Mount: HP-PM-NI

INDUSTRIAL APPROVALS

NEMA 4, 4X
UL-1950, CE, FCC Class 15, Part B

KEY SWITCH

MATERIAL: Industrial silicone rubber
LIFE: Greater than 10 million cycles
TRAVEL: 0.060" (1.5mm)
ACTUATION FORCE: 5 oz (130g)
FEEDBACK: Tactile with mechanical snap

POWER

5V@10ma (from mouse conn. port)

TEMPERATURE RANGE

-40F to +194F (-40C to +90C)

HUMIDITY: 100%

SHOCK

3x11 ms pulses of 50g on each of 3 axes

FLAMMABILITY

PRINTED CIRCUIT BOARD: 94 VO
SILICONE OVERLAY: 94 HB
INTERFACE CABLE: 94 VO

VIBRATION

POWER SPECTRAL DENSITY: 0.04g/Hz
FREQUENCY RANGE: 20Hz - 2kHz
DURATION OF TEST PER AXIS: 3 hours

DIMENSIONS:

(W-H-D) 4.5" x 4.5" x 1.0"
114.3mm x 114.3mm x 25.4mm

CABLE

LENGTH: 5 feet from mouse to Bulkhead Connector
DESIGN: Single PS/2 Bulkhead Cable

COMPATIBILITY

PS/2: All Windows Operating Systems

WARRANTY: 1 Year Limited Warranty

MODEL NUMBERS:

HP-DT-NI: With PS/2 cable



© 2005 IKEY, Ltd.

IKEY Industrial Peripherals
2621 Ridgpoint Drive, Suite 235
Austin, TX 78754
1.800.866.6506
www.ikey.com