



▶ Non-Incendive Keyboards

PM-5K-NI

Technical Specifications

Features and Benefits:

- ▶ 113-Key Functionality
- ▶ Integrated HulaPoint™ Pointing Device
- ▶ Meets NEMA 4, 4X Specifications
- ▶ Stainless Steel Bezel
- ▶ 20 Function Keys
- ▶ Industrial Silicone Rubber Keypad
- ▶ 10-Key Number Pad
- ▶ MS Windows™ Key
- ▶ Includes Bulkhead Connectors

INDUSTRIAL APPROVALS

NEMA 4, 4X
UL-1950, CE, FCC Class 15, Part B

KEY SWITCH

MATERIAL: Industrial silicone rubber
LIFE: Greater than 10 million cycles
TRAVEL: 0.060" (1.5mm)
ACTUATION FORCE: 5 oz (130g)
FEEDBACK: Tactile with mechanical snap

POWER

KEYBOARD: 5V@10ma (from CPU port)
HULAPOINT: 5V@10ma (from mouse conn. port)

TEMPERATURE RANGE

-40F to +194F (-40C to +90C)

HUMIDITY: 100%

SHOCK

3x11 ms pulses of 50g on each of 3 axes

FLAMMABILITY

PRINTED CIRCUIT BOARD: 94 VO
SILICONE OVERLAY: 94 HB
INTERFACE CABLE: 94 VO

VIBRATION

POWER SPECTRAL DENSITY: 0.04g/Hz
FREQUENCY RANGE: 20Hz - 2kHz
DURATION OF TEST PER AXIS: 3 hours

DIMENSIONS:

(W-H-D) 17.7" x 9.2" x 2.0"
449.6mm x 233.7mm x 50.8mm
CUTPIT: 16.4" x 7.9"

CABLE

LENGTH: 5 feet from keyboard to Bulkhead Connector
DESIGN: 2 cables (providing separate keyboard and mouse connections)

COMPATIBILITY

PS/2 KEYBOARD/HULAPOINT: All Windows Operating Systems

WARRANTY: 1 Year Limited Warranty

MODEL NUMBERS:

PM-5K-NI: With PS/2 cable

Also Available:

Desktop: DT-5K-NI



© 2005 IKEY, Ltd.