

# CK65

## Mobile Computer

The industry's most advanced ultra-rugged mobile computer that's ready for the toughest DC environments and the broadest range of workflows, the CK65 is designed to maximize worker productivity and minimize TCO.

In this environment of ever smaller orders and ever shrinking delivery timeframes, you need ways to improve your inventory accuracy and order cycle time. The CK65 is purpose-built to help with those objectives by maximizing worker productivity. The perfect blend of keypad and touchscreen, ergonomics and durability, the CK65 is light enough to be used all day yet durable enough to withstand the wear and tear of daily use. And with a 7,000 mAh extended smart battery, the CK65 is capable of up to 28 hours of continuous operation, so workers finding themselves with a dead battery in the middle of their shift will be a thing of the past.

Built on the Mobility Edge™ platform, the CK65 minimizes TCO like no other product on the market by future-proofing your investment with support through Android™ R and beyond, and accelerated provisioning to minimize your time to value. And with its ultra-rugged design that can withstand 3 m (10 ft) drops to concrete as well as being rated to IP65 and IP68, the CK65 is durable in even the toughest DC environments. The CK65 even offers cold storage models for freezer environments and non-incendive (NI)/ATEX models for areas with hazardous gases.

Honeywell's legacy of imaging innovation continues on the CK65 with the newest FlexRange FR imager. The FlexRange FR has a dual-lens architecture that simultaneously captures near, mid, and far range with no moving parts. It's the ultimate combination of speed, range, and ruggedness. From picking to the pallet to the rack, the FlexRange FR imager is capable of handling the broadest range of workflows. And without moving parts, there's no time spent re-focusing, so the FlexRange FR is always operating at lightning speed.



*Built on the Honeywell Mobility Edge platform, the ultra-rugged CK65 mobile computer combines touchscreen and keypad data input, real-time connectivity, and advanced data capture for industry-leading investment protection.*

### **DISINFECTANT-READY HOUSINGS - NEW!**

Select models now available with disinfectant-ready housings. These models can be cleaned regularly with a wide variety of cleaning solutions without damaging your product.

## FEATURES AND BENEFITS



The Mobility Edge hardware platform and enterprise lifecycle tools drive an integrated, repeatable, scalable approach for accelerated and secure development, deployment, performance management, and lifecycle management.



The CK65 device provides future-proof investment protection with support for four Android generations, starting with Android 8 (O). Security updates are also available for up to two years after the last Google patch through Honeywell Sentinel.



The large touchscreen with a 38- or 30-key numeric keypad with function keys or 51-key alphanumeric keypad supports both legacy key-centric and newer touch applications. Keypads allow input in extreme environments and optimize efficiency in all environments.



Rugged construction withstands multiple 3 m (10 ft) drops to concrete across the temperature range and 2,000 1.0 m (3.3 ft) tumbles. IP65 and IP68 ratings against dust and water spray.



Enhanced 1D/2D scanning/data capture for short, mid, or long range workflows, as well as direct part marking scan capabilities.

**Honeywell**

# CK65 Technical Specifications

## SYSTEM ARCHITECTURE

**Processor:** 2.2 GHz Qualcomm® 64-bit Snapdragon™ octa-core

**Operating System:** Android 8.0 Oreo (system compatible up to Android R)

**Memory:** 2 GB/4 GB DDR4 RAM, 32 GB Flash

**Display:** 10.16 cm (4 in) 480 x 800 bright color LCD with backlight, outdoor readable, optically bonded to touch panel

**Touch Panel:** Rugged multi-touch capacitive touch panel, optically bonded for extra durability and better sunlight viewability. Automatic detection and configuration utilizing mutual and self-capacitance modes for water rejection and use with many off-the-shelf gloves

**Keypad:** 51-key alpha or 38- or 30-key numeric keypad, plus two programmable side buttons

**Audio:** Speaker, microphone support with noise cancellation. PTT support and Bluetooth® wireless headset support

**I/O Ports:** Durable, custom I/O connector compatible with CK3 accessories

**Camera:** 13.0-megapixel color camera with autofocus and advanced software features for better image quality, f/2.0 aperture, flash LED with flashlight mode

**Sensors:** Ambient light sensor, accelerometer, gyroscope, hall effect

**Storage Expansion:** User-accessible microSD card up to 512 GB (SDXC/SDHC/SDIO-compliant)

**Battery:** Li-Ion, 7,000 mAh Smart Battery

**Hours of Operation:** 28 hours

**Scanning Capabilities:** Honeywell N6703 Slim Imager Engine (1D/2D); 6803FR FlexRange Slim Imager (1D/2D); Honeywell EX20 Near/Far Imager (1D/2D); Honeywell Scanning SDKs for Android

**Warranty:** One-year limited factory warranty

## MECHANICAL

**N6703SR/6803FR Version Dimensions:** 22.7 cm x 8.3 cm x 4.2 cm (8.9 in x 3.3 in x 1.7 in)

**N6703SR/6803FR Version Weight:** 498 g (17.6 oz) with battery pack

**EX20 Version Dimensions:** 22.7 cm x 8.3 cm x 4.7 cm (8.9 in x 3.3 in x 1.9 in)

**EX20 Version Weight:** 544 g (19.2 oz) with battery pack



## For more information:

Call Julianne: [800-830-9523](tel:800-830-9523) x115

Email [info@L-Tron.com](mailto:info@L-Tron.com)

L-Tron Corporation  
7911 Lehigh Crossing  
Suite 6, Victor, NY 14564  
[www.L-Tron.com](http://www.L-Tron.com)

## WIRELESS CONNECTIVITY

**WLAN:** IEEE 802.11 a/b/g/n/ac; Wi-Fi certified 2x2 MIMO support

**Additional WLAN Features:** 802.11 d/e/h/i/k/r/w

**WLAN Security:** OPEN, WEP, WPA/WPA2 (Personal and Enterprise)

**Supported EAP:** TLS, PEAP, TTLS, PWD, LEAP CCX Version 4 certified

**Bluetooth:** V5.0 with BLE and Backward Compatibility

**Bluetooth Profiles:** HFP, PBAP, A2DP, AVRCP, OPP, SPP, GATT

**NFC:** Integrated Near Field Communication

**VoIP:** Supported

**VPN:** IPsec V4/L2TP, PPTP

**Push to Talk (PTT):** Supported

## ENVIRONMENTAL

**Operating Temperature:**

**Standard Temp Unit:** -20°C to 50°C (-4°F to 122°F)

**Cold Storage Unit:** -30°C to 50°C (-22°F to 122°F)

**Storage Temperature:** -30°C to 70°C (-22°F to 158°F)

**Humidity:** 0 to 95% relative humidity (non-condensing)

**Drop:** 3 m (10 ft) to concrete at room temperature, 2.4 m (8 ft) across operating range per MIL-STD 810G

**Tumble:** 2,000 1.0 m (3.3 ft) tumbles per IEC 60068-2-32 specification

**ESD:** ±15 kV Air and ±8 kV Direct

**Environmental Sealing:** Independently certified to meet IP65 and IP68 standards for moisture and particle intrusion

## ADDITIONAL CERTIFICATIONS AND APPROVALS

### US/Canada:

Class 1 Div 2, Groups A, B, C, and D

Class 2 Div 2, Groups F, G

Class 3

T5, -20°C < Tamb < 50°C (-4°F to 122°F)

### ATEX:

Ex II 3G Ex ic op is IIC T5 Gc IP64

Ex II 3D Ex ic op is IIIB T100°C Dc IP64, -20°C < Tamb < 50°C

### IEC Ex:

Ex ic op is IIC T5 Gc IP64

Ex ic op is IIIB T100°C Dc IP64

-20°C < Tamb < 50°C

For a complete listing of all compliance approvals and certifications, please visit [www.honeywellaidc.com/compliance](http://www.honeywellaidc.com/compliance).

For a complete listing of all supported barcode symbologies, please visit [www.honeywellaidc.com/symbologies](http://www.honeywellaidc.com/symbologies).

Mobility Edge is a trademark or registered trademark of Honeywell International Inc.

Android is a trademark or registered trademark of Google LLC.

Qualcomm and Snapdragon are trademarks or registered trademarks of Qualcomm Incorporated.

Bluetooth is a trademark or registered trademark of Bluetooth SG, Inc.

All other trademarks are the property of their respective owners.



THE  
FUTURE  
IS  
WHAT  
WE  
MAKE IT

Honeywell